

## Motion detector

# IS 2180-2

EAN 4007841603816



## Functional description

The IS 2180-5 infrared motion detector's small brother is the ideal choice for watching over areas of up to 200 m². Not only impressing with top-class sensor technology as well, this one also pleases the eye with its modern design that fits perfectly into the overall picture on contemporary architecture. No exception here either: flexibility in adjusting coverage angle and reach.

## Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	120 x 78 x 55 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	passive infrared
Application, place	outdoors
Type of installation	Surface wiring
Switching zones	504 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Optimum mounting height	2 m
Detection angle	180 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	r = 5 m (39 m²) / r = 12 m (226 m²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	10 s – 15 min
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	6 stk.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	white

Motion detector

## IS 2180-2

EAN 4007841603816

### Sensorenerfassungsbereich 1

